



EN ISO 20345:2011



RITMO  
**MENEITO**  
91355-01

**S1 SRC**

**Size:** 35-48  
**Weight:** 500 gr.

**Fit:** 11

**Working Environment:**  
Finishing-off building, Logistics and Light Industry, Components and Automotive, ESD Areas



## FEATURES

### UPPER

MicroFiber Suede 1,6-1,8 mm  
Digitex Airy  
MicroFiber Suede with Pro-tech  
SXT light 1,6-1,8 mm

### LINING

3D Air circulation 320 gr.

### ANTISLIP LINING DUALMICRO

### INSOLE

Five 4 Fit

### TOE CAP

Alu SXT 2.0 Toe cap

### TYPE

Sandal

### SOLE

**PU / PU ESD-PLUS SRC**

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

## TECHNOLOGIES

### Removable Insole

**FIVE 4 FIT**

Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



### Protection elements

**alu-sxt 2.0**  
aluminium

The result of the evolution of the latest aluminium technologies. A new multi-thicknesses toe cap, which delivers a highly performing protection where needed. Ultralight protection, keeping comfortable inner volumest.



### Lateral stability

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### Other

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



## SRC (SRA+SRB)



SOLE 91  
PU - PU

|   |   |             |
|---|---|-------------|
| <b>SRA</b><br>CERAMIC<br>+<br>DETERGENT<br>SOLUTION | FLAT<br>≥0.32<br>HEEL<br>(CONTACT ANGLE °)<br>≥0.28 | <b>0.54</b> |
| <b>SRB</b><br>STEEL<br>+<br>GLYCEROL                | FLAT<br>≥0.18<br>HEEL<br>(CONTACT ANGLE °)<br>≥0.13 | <b>0.29</b> |
|   |   | <b>0.23</b> |

EN ISO 20344:2011