



EN ISO 20345:2011



RITMO
PASITOS
91253-01L

S1P SRC

Size: 35-48
Weight: 550 gr.

Fit: 11

Working Environment:
Finishing-off building, Logistics and Light Industry, Components and Automotive, ESD Areas



FEATURES

UPPER

Drummed Suede Leather Hydro 1,6-1,8 mm
Nubuk Leather Hydro 1,6-1,8 mm

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU / PU ESD-PLUS SRC

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

TECHNOLOGIES

Removable Insole



Highly breathable and absorbent anatomic insole. Multilayer structure to take advantage of the peculiarities of each component. Dry and with a comfortable memory foam "pillow"



Protection elements



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



SRC (SRA+SRB)



		SOLE 91 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.54
	HEEL (CONTACT ANGLE 1°) ≥0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.29
	HEEL (CONTACT ANGLE 1°) ≥0.13	0.23

EN ISO 20344:2011