



EN ISO 20345:2011



SCOUT  
**ORTLES**  
30335-00L

**S3 \*CI HRO HI SRC**

**Size:** 36-50  
**Weight:** 680 gr.

**Fit:** 11

**Working Environment:**  
Building, Wood-metal carpentry,  
Farming and Gardening



**FEATURES**

**UPPER**

MicroFiber Suede 1,8-2,0 mm  
No ladder H.T. Fabric  
MicroFiber TOP 1,8-2,0 mm  
Reflex insert

**LINING**

3D Air circulation 320 gr.

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

Qrs01

**TOE CAP**

Alu SXT 2.0 Toe cap

**RESISTANCE TO PERFORATION**

KX Antiperforation PS

**TYPE**

Low Shoe

**SOLE**

**PU-RUBBER VIBRAM-FIRE&ICE**

PU foam insole, light and comfortable. Modular overtoe to protect uppers. VIBRAM rubber tread with Fire & ICE mix for high performance in all temperatures. Self-cleaning design with special SRC grip.

**TECHNOLOGIES**

**Removable Insole**



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



**Protection elements**



Toecap "Alu Sxt 2.0" with differentiated thicknesses, resistant to 200J. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



**Lateral stability**



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



**Other**



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.



**SRC (SRA+SRB)**



		SOLE 30 PU - RUBBER
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	<b>0.53</b>
	HEEL (CONTACT ANGLE °) ≥0.28	<b>0.49</b>
SRB STEEL + GLYCEROL	FLAT ≥0.18	<b>0.23</b>
	HEEL (CONTACT ANGLE °) ≥0.13	<b>0.18</b>

EN ISO 20344:2011