



EN ISO 20344:2011



SKIPPER LADY  
**BELVEDERE**  
95416-01

**S1 SRC**

**Size:** 35-42 Lady  
**Weight:** 415 gr.

**Fit:** 11

**Working Environment:**  
Logistics and Light Industry,  
Components and Automotive, ESD  
Areas



## FEATURES

### UPPER

Digitex Airy  
MicroFiber Suede with Pro-tech  
SXT light

### LINING

Breezy 3D, two-layers  
combination

### ANTISLIP LINING

DUALMICRO

### INSOLE

Five 4 Fit "lady"

### TOE CAP

Alu SXT 2.0 Toe cap

### TYPE

Sandal

### SOLE

#### PU DUAL-DENSITY SRC

Double density PU outsole with  
tread designed mainly for indoor  
use. Self-cleaning design and  
highly non-slip grip. SRC Antislip  
standard.

## TECHNOLOGIES

### Removable Insole

**FIVE 4 FIT**  
LADY.

Highly breathable and absorbent  
anatomic insole. Multilayer structure  
to take advantage of the peculiarities  
of each component. Dry and with a  
comfortable memory foam "pillow"



### Protection elements

**alu-sxt 2.0**  
aluminium

The result of the evolution of the  
latest aluminium technologies. A new  
multi-thicknesses toe cap, which  
delivers a highly performing  
protection where needed. Ultralight  
protection, keeping comfortable inner  
volumest.



### Lateral stability

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It  
houses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.



### Torsional stability

**STABIL ACTIVE**

Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.



### Electrical features



ESD footwear discharge static  
electricity and avoid damaging  
surrounding objects; they are  
designed in compliance with the  
following standards: IEC EN  
61340-5-1:2016 - IEC EN  
61340-4-3:2018 - IEC EN  
61340-4-5:2018.

### Other

Strip with 4 filaments of carbon fiber,  
ensuring proven anti-static properties  
of the footwear over time.



## SRC (SRA+SRB)

		SOLE 95 PU - PU
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.38</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.21</b>
		<b>0.24</b>

EN ISO 20344:2011