



EN ISO 20347:2012 

SKIPPER LADY
CIMA
96398-05
02 FO SRC

Size: 35-42 Lady
Weight: 360 gr.

Fit: 11

Working Environment:
 Multipurpose, Components and Automotive



FEATURES

UPPER
 Digitex Hydro Airy
 MicroFiber Suede 1,6-1,8 mm
 Digitex Hydro Airy
 MicroFiber Suede with Pro-tech
 SXT light 1,6-1,8 mm

LINING
 Breezy 3D, two-layers
 combination


ANTISLIP LINING
 DUALMICRO

INSOLE
 Five 4 Fit

TOE CAP

TYPE
 Low Shoe

SOLE
PU DUAL-DENSITY SRC
 Double density PU outsole with
 tread designed mainly for indoor
 use. Self-cleaning design and
 highly non-slip grip. SRC Antislip
 standard.



SRC (SRA+SRB)

| | | | |
|--|-------------------------------------|--------------------|-------------------|
| | | SOLE 95 PU - PU | |
| SRA CERAMIC + DETERGENT SOLUTION | FLAT ≥0.32 | 0.38 | EN ISO 20344:2011 |
| | HEEL (CONTACT ANGLE °°) ≥0.28 | | |
| SRB STEEL + GLYCEROL | FLAT ≥0.18 | 0.21 | |
| | HEEL (CONTACT ANGLE °°) ≥0.13 | | |

TECHNOLOGIES

Removable Insole
FIVE 4 FIT

Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"



Protection elements
EN ISO 20347:2012

Puncture resistant recycled non-
 metallic insert plus 1100N.

Lateral stability
dynamic HC control
 technology

Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.



Torsional stability
STABIL ACTIVE

Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.



Electrical features


ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other
DUALMICRO
DUALWICRO

Double non-slip layer of microfibre,
 resistant up to 200,000 cycles. Makes
 the footwear more comfortable,
 blocking the foot during use.